Technical Data
Chevron

PROJECT FLOORS

Covering type according to EN ISO 10582	Heterogeneous Plankwood, Typ 1
Number of colours	8 planks
Dimensions of Planks	457x102x2,5 mm
Packaging per box/pallet	3.34 m²/200.40 m²
Performance classification EN ISO 10582 / ISO 10874	23, 33, 42
Total thickness ISO 24346	2.5 mm
Wearlayer thickness ISO 24340	0.55 mm
Surface treatment	yes/PU
Bevelled edges	Yes
Total weight ISO 23997	3.81 kg/m²
Residual indentation ISO 24343-1	≤ 0.1 mm*
Dimensional stability ISO 23999	≤ 0.15%*
Castor chair suitability ISO 4918	yes – using EN 12529, Typ W
Underfloor heating EN 1264-2	suitable up to 29°C
Behaviour to fire EN 13501-1	Bfl-s1
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m² K/W
Electrical propensity when walked upon EN 1815	< 2 k/V
Impact sound improvement ISO 10140-3	4 dB
Colour fastness to artificial light ISO 105-B02/2	≥ 7
Electrostatic characteristics EN 1081	> 10^{12}
Chemical resistance ISO 26987	conforms**
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)
Adhesive recommendation	see installation instruction
Maintenance/Cleaning recommendation	Dr. Schutz

* Averaged value
** Vis-à-vis the short-term effects of normal, domestic agents.

(Date: 01.01.2023)

Please also note the installation and cleaning and care instructions.



PROJECT FLOORS GmbH ◦ Von-Klespe-Str. 1 ◦ Grube Carl ◦ D-50226 Frechen
Telefon +49 (0) 2233 9687-0 ◦ Fax +49 (0) 2233 9687-10 ◦ www.project-floors.com ◦ info@project-floors.com