

Technical Data

Groutline



PROJECT

FLOORS

| | |
|---|---|
| Covering type according to EN ISO 10582 | Heterogeneous Planks, Type 1 |
| Number of colours | 6 planks |
| Dimensions of Planks | 1219x228/152/76x2,5 mm (contents per box: 6 planks each width) |
| Packaging per box/pallet | 3.34 m ² /200.40 m ² |
| Performance classification EN ISO 10582 / ISO 10874 | 23, 33, 42 |
| Total thickness ISO 24346 | 2.5 mm |
| Wearlayer thickness ISO 24340 | 0.55 mm |
| Surface treatment | yes/PU |
| Bevelled edges | Yes |
| Total weight ISO 23997 | 3.81 kg/m ² |
| Residual indentation ISO 24343-1 | ≤ 0.1 mm* |
| Dimensional stability ISO 23999 | ≤ 0.15%* |
| Castor chair suitability ISO 4918 | yes – using EN 12529, Typ W |
| Underfloor heating EN 1264-2 | suitable up to 28°C |
| Behaviour to fire EN 13501-1 | Bfl-s1 |
| Resistance to thermal conductivity ISO 8302 / EN 12667 | 0.02 m ² K/W |
| Electrical propensity when walked upon EN 1815 | < 2 kV |
| Impact sound improvement ISO 10140-3 | 4 dB |
| Colour fastness to artificial light ISO 105-B02/2 | ≥ 7 |
| Electrostatic characteristics EN 1081 | > 10 ¹² |
| Chemical resistance ISO 26987 | conforms** |
| Slip resistance | R9 to R10 (depending on design resp. emboss: details available on request) |
| Adhesive recommendation | see installation instruction |
| Maintenance/Cleaning recommendation | Dr. Schutz |

* Averaged value

** Vis-à-vis the short-term effects of normal, domestic agents.

(Date: 01.01.2019)

Please also note the installation and cleaning and care instructions.

