

## Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient )	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

## Floor Covering Installation

Covering/Collection	Adhesive	Tool/trowel acc. TKB	approx. consumption g/m <sup>2</sup>	Remark
Design Floor				
floors@home 20 floors@home 30 floors@home 40 floors@work 55 floors@work 80	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A1	250 - 300 g/m <sup>2</sup>	
	<b>SCHÖNOX® iFLOOR®</b> Dispersion based rollable adhesive	Role	80 g/m <sup>2</sup>	
	<b>SCHÖNOX® PROTECT</b> Universal adhesive for highest loads	TKB A4	ca. 250 g/m <sup>2</sup>	<b>In wet areas or areas with increase heat development (like shop windows, winter gardens)</b>

All adhesive fulfill EC1 PLUS acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +49 (0) 2547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.project-floors.com](http://www.project-floors.com).