

Cleaning and care instructions

ECO+ COLLECTION



1. General information

PROJECT FLOORS Design Flooring provides products with a polyurethane coating already applied at factory level. Regular cleaning is necessary to maintain the optimal appearance of our products over the long term and to ensure a long life. This will depend on the area of application and how often it is frequented, as well as on the choice of colour and the surface embossing of the decor.

2. Preventative measures

In order to protect the flooring from mechanical damage caused by the introduction of dirt, water, sand, etc., it is advisable to establish appropriate clean-off zones. During the construction phase, it is necessary to protect the flooring from mechanical damage caused by other trades.

3. Cleaning on completion of construction work

Once construction work is complete, it is necessary to clean the work area to ensure that any building waste and adhesive residue is completely removed. This process is not the same as basic cleaning (see point 6).

In accordance with the adhesive drying times specified by the manufacturer, the floor covering must be cleaned by using PU cleaner or basic cleaner diluted with water (according manufacturer recommendation). The waste cleaning water must be completely absorbed and the floor then neutralised with adequate amounts of clear water.

4. Initial treatment

Because the surface coating has already been applied, an initial treatment is not absolutely necessary. As long as the drying times of the adhesive are respected, the laid area can be walked on immediately.

5. Day-to-day cleaning and maintenance care

Day-to-day cleaning in this case means manual cleaning using a conventional mop. The coarse dirt must firstly however be removed by means of a broom or vacuum cleaner. The area can then be damp-wiped with a PU cleaner in accordance with the instructions provided. Affix felt pads to provide extra protection against score marks and scratches from movable furniture. Office chairs that are to be used with PROJECT FLOORS floor coverings must be equipped with type W soft castors conforming to DIN 68131.

6. Removal of stains, heel marks and scratches

Stubborn stains and rubber heel marks that cannot be removed with routine cleaning and maintenance methods can be removed with the recommended product in conjunction with a cloth or non-scratch pad. Then wipe with clean water. Remove stains as soon as possible, as certain types of stains become embedded in the floor covering as it ages and can then only be removed with difficulty or incompletely.

7. Basic cleaning

Depending how dirty it is, the floor can be cleaned intermittently with the basic cleaner R (Dr. Schutz), which must be diluted in accordance with the manufacturer's recommendations. Once the waste cleaning water has been completely absorbed, the flooring is neutralised with clear, warm water until all dirt and cleaning residue have been completely removed. In the case of larger areas, the use of cleaning and treatment machines is recommended.

If treatment products from another manufacturer are used, their application must be in line with the advice of that particular manufacturer. If you have any further questions concerning the cleaning and care of flooring, please contact customer service at Dr. Schutz, Bonn Tel.: +49 228 95352 0, Fax: +49 228 95352 28 or look online at www.dr-schutz.com.

By providing these cleaning and care instructions, the floor layer fulfils his obligations in accordance with DIN 18365. You can find the latest information about cleaning and care at www.project-floors.com in the „Downloads“ section.

8. Important information

Conservation of value:

Cleaning measures - especially regular ones - with a high level of moisture, puddle formation and long-term standing wetness should be avoided if possible. In order to minimise the influence of moisture on the seam areas and bonding of adjacent panels, the cleaning solution can be sprayed evenly onto the floor, e.g. with a pressure pump sprayer or similar.

Colouring products (e.g. hair dyes, wound disinfectants) as well as plasticiser migration (e.g. from rubber, carpet underlays) can lead to irreversible discolouration of the surface. Therefore, avoid contact with these products.

For additional protection from scuffing and scratches caused by the movement of furniture, the use of felt pads is required. Office chairs intended for use on PROJECT FLOORS floor coverings must be fitted with soft double castors type W (soft), in accordance with DIN 68131.



With this QR code you will find further or new versions of this and other documents

Version dated 04/2023 replaces all preceding versions. Applies until further notice. The contents are based on current expertise and have been produced based on the best knowledge available to us and in good faith. This document can be modified, added to or replaced at any time without notification. You must check if it is the latest version at www.project-floors.com or contact one of our employees

