

# Technical data ECO+ COLLECTION

# PROJECT FLOORS

Covering type according to DIN EN 14565	Heterogeneous elements in plank / tiles format
Number of colours	14 planks / 6 tiles
Packaging per box/pallet	3.34 m <sup>2</sup> /200.40 m <sup>2</sup> 600x600 mm: 3.24 m <sup>2</sup> /194.40 m <sup>2</sup>
Performance classification EN ISO 10582 / ISO 10874	23, 32
Total thickness ISO 24346	2.5 mm
Wearlayer thickness ISO 24340	0.3 mm
Surface treatment	yes/PU
Bevelled edges	ja
Total weight ISO 23997	4.08 kg/m <sup>2</sup>
Residual indentation ISO 24343-1	≤ 0.02 mm*
Dimensional stability ISO 23999	≤ 0.10%*
Castor chair suitability ISO 4918	yes – using EN 12529, type W
Underfloor heating EN 1264-2	suitable
Behaviour to fire EN 13501-1	Cfl-s1
Resistance to thermal conductivity ISO 8302/ EN 12667	0.007 m <sup>2</sup> K/W
Electrical propensity when walked upon EN 1815	< 2.9 k/V
Impact sound improvement ISO 10140-3	2 dB
Colour fastness to artificial light ISO 105-B02/02	≥ 7
Electrostatic characteristics EN 1081	> 10 <sup>12</sup>
Chemical resistance ISO 26987	conforms **
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)
Scratch resistance EN ISO 14565	passed
Adhesive recommendation	according to installation instruction / recommendation of the adhesive manufacturer
Emission performance COV	A+
Environment RAL/Blauer Engel	achieved
Environment BREEAM/Green Guide/LEED	achieved (conforms to Indoor Air Comfort Gold)
Maintenance/Cleaning recommendations	Dr. Schutz

\* Averaged value

(Date: 01.10.2023)

\*\* Vis-à-vis the short-term effects of normal, domestic agents.

### Please also note the installation and cleaning and care instructions.

Version dated 01.10.2023 replaces all preceding versions. Applies until further notice. The contents are based on current expertise and have been compiled based on the best knowledge available to us and in good faith. This document can be modified, added to or replaced at any time without notification. Please check if this is the latest version at <http://www.project-floors.com> or contact one of our employees.

