

# Technical Data HERRINGBONE 30

# PROJECT FLOORS

Covering type according to EN ISO 10582	Heterogeneous Planks, Type 1
Number of colours	5 planks
Dimensions of Planks	457x76 mm
Packaging per box/pallet	3.34 m <sup>2</sup> /240.48 m <sup>2</sup>
Performance classification EN ISO 10582 / ISO 10874	23, 31
Total thickness ISO 24346	2.0 mm
Wearlayer thickness ISO 24340	0.3 mm
Surface treatment	yes/PU
Bevelled edges	No
Total weight ISO 23997	3.51 kg/m <sup>2</sup>
Residual indentation ISO 24343-1	≤ 0.1 mm*
Dimensional stability ISO 23999	≤ 0.15%*
Castor chair suitability ISO 4918	yes – using EN 12529, Typ W
Underfloor heating EN 1264-2	suitable up to 29°C
Behaviour to fire EN 13501-1	Bfl-s1
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m <sup>2</sup> K/W
Electrical propensity when walked upon EN 1815	< 2 kV
Impact sound improvement ISO 10140-3	2 dB
Colour fastness to artificial light ISO 105-B02/2	≥ 7
Electrostatic characteristics EN 1081	> 10 <sup>12</sup>
Chemical resistance ISO 26987	conforms**
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)
Adhesive recommendation	see installation instruction
Maintenance/Cleaning recommendation	Dr. Schutz

\* Averaged value

(Date: 01.02.2024)

\*\* Vis-à-vis the short-term effects of normal, domestic agents.

**Please also note the installation and cleaning and care instructions.**

