Technical Data
floors@home

	floors@home/20	floors@home/30
Covering type according to ISO 10582	Heterogeneous Planks / Tiles, type 1	
Number of colours	30 planks	58 planks / 22 tiles
Packaging per box/pallet	3.34 m²/240.48 m² 600x600 mm: 3.24 m²/233.28 m²	
Performance classification EN ISO 10582 / ISO 10874	22	23, 31
Total thickness ISO 24346	2.0 mm	
Wearlayer thickness ISO 24340	0.2 mm	0.3 mm
Surface treatment	ja/PU	
Bevelled edges	nein	ja (dekorabhängig)
Total weight ISO 23997	3.20 kg/m²	3.51 kg/m²
Residual indentation ISO 24343-1	≤ 0.1 mm*	
Dimensional stability ISO 23999	≤ 0.15 %*	
Castor chair suitability ISO 4918	yes – using EN 12529, type W	
Underfloor heating EN 1264-2	suitable up to 29°C	
Behaviour to fire EN 13501-1	Bfl-s1	
Resistance to thermal conductivity ISO 8302/ EN 12667	0.02 m² K/W	
Electrical propensity when walked upon EN 1815	< 2 k/V	
Impact sound improvement ISO 10140-3	2 dB	
Colour fastness to artificial light ISO 105-B02/02	≥ 7	
Electrostatic characteristics EN 1081	> 10^{12}	
Chemical resistance ISO 26987	conforms**	
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)	
Adhesive recommendation	see installation instruction	
Maintenance/Cleaning recommendation	Dr. Schutz	

* Averaged value
** Vis-à-vis the short-term effects of normal, domestic agents.

(Date: 01/01/2023)

Please also note the installation and cleaning and care instructions.

PROJECT FLOORS GmbH ◦ Von-Klespe-Str. 1 ◦ Grube Carl ◦ D-50226 Frechen
Telefon +49 (0) 2233 9687-0 ◦ Fax +49 (0) 2233 9687-10 ◦ www.project-floors.com ◦ info@project-floors.com