

# Product specifications for floors@home

# PROJECT FLOORS

\_\_\_\_\_ m<sup>2</sup>

Heterogeneous LVT floor covering PROJECT FLOORS GmbH  
floors@home

### **Tiles**

457x305 or 457x457 or 610x305 or 600x600 or 914x457 mm

Wear layer: 0.4 mm  0.3 mm  0.2 mm

Total thickness: 2.0 mm

Name and colour refer to sample folder:

---

Performance classification EN ISO 10582 / ISO 10874:

0.4 mm wear layer: 23, 32, 41

0.3 mm wear layer: 23, 31

0.2 mm wear layer: 22

Reaction to fire: Bfl-s1

No phthalate plasticiser Hexamoll® DINCH®

The product requires professional installation and permanent bonding with a solvent free dispersion adhesive as recommended by the floor covering supplier.

\_\_\_\_\_ €/m<sup>2</sup>

---

\_\_\_\_\_ m<sup>2</sup>

Heterogeneous LVT floor covering PROJECT FLOORS GmbH  
floors@home

### **Plankwood**

914x102 or 914x152 or 914x228 or 1219x183 or 1219x228 mm

Wear layer: 0.4 mm  0.3 mm  0.2 mm

Total thickness: 2.0 mm

Name and colour refer to sample folder:

---

Performance classification EN ISO 10582 / ISO 10874:

0.4 mm wear layer: 23, 32, 41

0.3 mm wear layer: 23, 31

0.2 mm wear layer: 22

Reaction to fire: Bfl-s1

No phthalate plasticiser Hexamoll® DINCH®

The product requires professional installation and permanent bonding with a solvent free dispersion adhesive as recommended by the floor covering supplier.

\_\_\_\_\_ €/m<sup>2</sup>



Förderkreismitglied im  
bund deutscher  
innenarchitekten