Product specifications for floors@work



Heterogeneous LVT floor covering PROJECT FLOORS GmbH m² floors@work Tiles 457x305 or 457x457 or 610x305 or 600x600 or 914x457 mm Wear layer: 0.55 mm Total thickness: 2.5 mm Name and colour refer to sample folder: Performance classification EN ISO 10582 / ISO 10874: 0.55 mm wear layer: 23, 33, 42 Reaction to fire: Bfl-s1 No phthalate plasticiser Hexamoll® DINCH® The product requires professional installation and permanent bonding with a solvent free dispersion adhesive as recommended by the floor covering supplier. €/m² m² Heterogeneous LVT floor covering PROJECT FLOORS GmbH floors@work Plankwood 457x457 or 914x102 or 914x152 or 914x228 or 1219x183 or 1219x228 mm Wear layer: 0.55 mm Total thickness: 2.5 mm Name and colour refer to sample folder: Performance classification EN ISO 10582 / ISO 10874: 0.55 mm wear layer: 23, 33, 42 Reaction to fire: Bfl-s1 No phthalate plasticiser Hexamoll® DINCH® The product requires professional installation and permanent bonding with a solvent free dispersion adhesive as recommended by the floor covering supplier.





_€/m²





Förderkreismitglied im

bund deutscher innenarchitekten