

# Product specifications for LOOSE-LAY/30

# PROJECT FLOORS

\_\_\_\_\_ m<sup>2</sup>

Heterogeneous LVT floor covering PROJECT FLOORS GmbH  
Collection LOOSE-LAY/30

### Tiles

457x457 mm, 610x305 mm or 600x600 mm

Wear layer: 0.3 mm

Total thickness: 4.2 mm

Name and colour refer to sample folder:

Performance classification EN ISO 10582 / ISO 10874:  
23/31

Reaction to fire: Bfl-s1

No phthalate plasticiser Hexamoll® DINCH®

The product requires professional installation with underlay LL UL 1000.

\_\_\_\_\_ €/m<sup>2</sup>

\_\_\_\_\_ m<sup>2</sup>

Heterogeneous LVT floor covering PROJECT FLOORS GmbH  
Collection LOOSE-LAY/30

### Plankwood

457x457 mm, 610x305 mm or 600x600 mm

Wear layer: 0.3 mm

Total thickness: 4.2 mm

Name and colour refer to sample folder:


Performance classification EN ISO 10582 / ISO 10874:  
23/31

Reaction to fire: Bfl-s1

No phthalate plasticiser Hexamoll® DINCH®

The product requires professional installation with underlay LL UL 1000.

\_\_\_\_\_ €/m<sup>2</sup>



Förderkreismitglied im  
bund deutscher  
innenarchitekten